

### General description

- Strong and stable framework of cabinet, which has the mounting holes
- The side panel and rear panel are the double-panel designed, the panels are fixed by the bolt from the inner.
- Between the inside and outside side panel has the inter space, which provides the channel to ventilate and support the enclosure internal heat exchange, and also can reduce the influence of the sunlight illumination
- The roof panel has the awning all around stretches out to keep from the rain, the bottom of awning have holes to keep the integrity well ventilated, which guarantees the air exchange.
- The bottom have cable entrance with rubber ring
- The enclosure is the 19" structure, also can install the mounting panel
- The top loaded with fans to ventilate, two sides panels have the blind holes to output heat



### Standard

Comply with IEC60950-1 IEC60529 and GB4208-93 standard.

### Material

All Material are high-quality SECC  
Thickness : mounting profile 1.2 mm; others : 1.0 mm



### Surface Finish

Degreasing, pickling, phosphoric, powder coated,

### Color

RAL 7035SN grey

### Size

<b>Height</b>	9U	18 U
<b>Width</b>	600 mm	
<b>Depth</b>	450 mm , 600 mm	600 mm , 600 mm

**Could be Customized**



### Standard accessories

- Metal front door with three points bolted lock.
- 4 PCS mounting profile.
- Top have 4 hooks,
- 2 PCS fans with power line,
- 15 sets cage&nuts.

### Optional accessories

Cable management,shelf,blank panel, power distribution unit, etc.

### Package

1PC/CTN.(Packed with waterproof plastic bag and have 8pcs corner protection.)  
Could be Customized

