

General description

- 1.Vented front and rear door with excellent ventilation rate above 70%;
- 2.Removable side panels with lock optional;
- 3.Adjustable cable entry on the top and bottom cover;
- 4.Welded steel frame for front and back part, flat packing is available;
- 5.S-shaped mounting profile, free to move forward and back;
- 6.Various optional accessories for common using;

Standard

ANS/EIA RS-310 -D,IEC297 - 2, DIN41491, PART1, DIN41491, PART7, ETSI Standard

Material

SPCC quality cold rolled steel
Thickness:mounting Profile:2.0mm,Others:1.2mm
Tempered glass Thickness:5mm

Degree of protection

IP20

Surface Finish

Degreasing,Pickling,Phosphating,Powder Coated

Loading Capacity

Static loading: 800kg(on the adjustable feet)



Flaax Server Cabinet

| Size | Width/mm | Depth/mm | height/mm |
|------|----------|----------|-----------|
| 22U | 600 | 600 | 1166 |
| 22U | 600 | 1000 | 1166 |
| 32U | 600 | 800 | 1610 |
| 32U | 800 | 1000 | 1610 |
| 42U | 800 | 800 | 2055 |
| 42U | 800 | 1000 | 2055 |

Network cabinets ordering table

| Cabinet Type | | Height | | - | Width | | Depth | | Front Door/Rear Door | |
|----------------|------|---------------|-----------|---|---------|-------|--------------|----------|------------------------|------|
| | Code | | Code | | | Code | | Code | | Code |
| Wallmount | W | 4U,9U,12U,18U | 4,9,12,18 | - | 600 | 60 | 450,600 | 45,60 | Single Glass door | G |
| Floor standing | F | 22U,32U,42U | 22,32,42 | | 600,800 | 60,80 | 600,800,1000 | 60,80,10 | Single Perforated Door | P |
| Server Rack | S | 22U,32U,42U | 22,32,42 | | 600,800 | 60,80 | 600,800,1000 | 60,80,10 | Single Metal Door | M |
| Outdoor | O | 9U,18U | 9,18 | | 600 | 60 | 450,600 | 45,60 | Split Glass door | SG |
| | | | | | | | | | Split Perforated Door | SP |
| | | | | | | | | | Split Metal Door | SM |

SKU example: 22U Floor standing cabinet, 600 x 450 With single Glass Front Door/ Single Rear Metal Door

F22-6045-GM