

General description

- Steel frame with Powder coated profiles
- Easy installation (no need of professional skills or tools)
- Excellent air ventilation design with cooling fans unit
- Removable side panels (optional lock) for convenient installation and maintenance
- Maximum static loading capacity of 100 kg
- L-shaped mounting profile, easy adjustable on the mounting rail
- Perfect solution for any 19-inch standard installation.
- Flat package design and supply, makes this cabinet easy to store and to transport
- Various optional accessories can be offered on request

Standard

Complies with: IEC60297-3, CE-EMC, CE-LVD, RHOS, TUV and ISO-9001 standards

Material

- Steel used is high quality Cold Rolled SPCC
- Thickness:
 - Front Door - Tempered glass: 5 mm
 - Frame, back, sides, top and bottom - Steel: 1.2 mm

Degree of protection

IP44

Surface finish

Degreasing, Powder coated (static Powdered)

Color

RAL9004/RAL9005(Black)



Size

Height: 4U-18U
Width: 600mm
Depth: 450mm/600mm



Standard Accessories

- 1pc Top and Bottom panels
- 1pc Glass Front door
- 1pc Metal Rear panel
- 2pc Side panel with latches
- 4pc Vertical Mounting profile
- 2pc Frame
- 15x cage & nuts set
- 1/2pc Fan unit depending on the cabinet size



Optional Accessories

- Horizontal Cable management
- Horizontal Blank Panels
- Various depths of Shelves
- Power distribution unit
- Cage nut set
- Thermostat Unit

Package

1pc/CTN

Flaax Wall-Mount Cabinet				
Part Number	Size	Width/mm	Depth/mm	height/mm
W6-6045	4U	600	450	290
W9-6045	9U	600	450	501
W9-6060	9U	600	600	501
W12-6045	12U	600	450	635
W12-6060	12U	600	600	635
W18-6060	18U	600	600	901